



Mid Norfolk Canopies & Trailers Ltd are agents for the Meredith and Eyre Trailer range.

## 2012 Series - Goods Trailers

500kg & 750kg GVW

***There are 12 Models in the 2012 range of 6' 6" x 4' (2 metres x 1.2 metres) Goods Trailers with a choice of 2 weights, 3 tyre sizes, and with a drop down tailgate or ramp to suit your requirements***



MEG7564TRM (Above) fitted with 145 R 13 Tyres, Loading Ramp, Weld Mesh Side Extension Kit and Rear Prop Stand Options



MEG7564WRM fitted with 20.5 x 8-10 Tyres, Loading Ramp and Weld Mesh Side Extension Kit, with Cast Coupling, Jockey Wheel and Rear Prop Stand Options.



Ladder Racks and Versatile Weld Mesh Side Extension Kits are available for both the Tailgate and Ramp Versions

STANDARD SPECIFICATION			
	MEG5064S	MEG7564W	MEG7564T
MAXIMUM GROSS WEIGHT	500kg	750kg	750kg
PAYLOAD	340kg (with Tailgate) 325kg (with Ramp)	575kg (with Tailgate) 560kg (with Ramp)	575kg (with Tailgate) 560kg (with Ramp)
MODEL DESIGNATION	MEG5064S with Tailgate MEG5064SR with Ramp MEG5064SM with Tailgate & Mesh MEG5064SRM with Ramp & Mesh	MEG7564W with Tailgate MEG7564WR with Ramp MEG7564WM with Tailgate & Mesh MEG7564WRM with Ramp and Mesh	MEG7564T with Tailgate MEG7564TR with Ramp MEG7564TM with Tailgate & Mesh MEG7564TRM with Ramp & Mesh
LENGTH (INTERNAL)	1985mm	1985mm	1985mm
WIDTH (INTERNAL)	1220mm	1220mm	1220mm
WIDTH (EXTERNAL)	1660mm	1745mm	1660mm
HEIGHT OF SIDES	305mm	305mm	305mm
LOADING HEIGHT	390mm	405mm	405mm
TYRE SIZE	S = 145 R 10	W = 20.5 x 8 - 10	T = 145 R 13
<b>SEE PRICE LIST FOR FULL EQUIPMENT LEVELS &amp; OPTIONS</b>			

The 2012 range of Unbraked Trailers have a strong A-frame drawbar arrangement, with a Lockable 50mm Ball Coupling as standard.

The durability of heavy duty, low maintenance rubber torsion axle has been proven in the Construction Plant industry and it has soft ride characteristics ideal for when the trailer is empty.

The Floor of the trailer is made from slip resistant high density plywood with a tough, waterproof resin coating on both sides.



145 R 10 Tyre fitted to MEG5064S



Optional Cast Coupling and Jockey Wheel shown on MEG7564WRM with 20.5 x 8 - 10 Tyres



Standard Pressed Steel Coupling and Prop Stand shown on MEG7564T Breakaway Cable fitted as Standard on all Unbraked Trailers

## UNBRAKED TRAILERS – THE LAW

To use an unbraked trailer rated at 750kg the towing vehicle must weigh at least 1500kg and at 500kg the towing vehicle must weigh at least 1000kg.

This is because the maximum gross weight of an unbraked Trailer must not exceed 50% of the kerbside weight of the towing vehicle – check the vehicle handbook for the maximum unbraked trailer weight permissible.

## Mid Norfolk Canopies & Trailers Ltd

Dereham Road | Scarning | Dereham | Norfolk NR19 2PG

Tel: 01362 687297 / 687257 | Fax: 01362 687258 | Email: info@midnorfolktrailers.co.uk | Web: www.midnorfolktrailers.co.uk

Director: G. A. Long | Dimensions & weights are given as a guide only. We reserve the right to alter specifications without notice